

UTILITY PATENT APPLICATION TRANSMITTAL

Only for new nonprovisional applications under 37 CFR 1.53(b)

Attorney Docket No. FL-1064

First Named Inventor or Application Identifier

GREG A. WESTBROOK, et al.

Express Mail Label No. EJ369014356US

Express Mailing Date SEPTEMBER 17, 1999

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☒ Fee (Authority to charge deposit account below.)
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages 28]
(preferred arrangement set forth below)
- Descriptive title of the invention
- Cross References to Related Applications (if needed)
- Statement Regarding Fed sponsored R & D (if needed)
- Reference to Microfiche Appendix (if filed)
- Background of the Invention
- Brief Summary of the Invention
- Brief Description of the Drawings (if filed)
- Detailed Description
- Claim(s)
- Abstract of the Disclosure
3. ☐ Drawing(s) (35 USC 113) [Total Sheets 0]
4. ☒ Oath or Declaration [Total Pages 1]
a. ☒ Newly unexecuted (original or copy)
b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 14 completed)
i. ☐ **DELETION OF INVENTORS**
Signed Statement below at 15 deleting
inventor(s) named in the prior application,
see 37 CFR 1.63(d)(2) and 1.33(b).
5. ☐ Incorporation by Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from which a
copy of the oath or declaration is supplied under Box 4b, is
considered as being part of the disclosure of the
accompanying application and is hereby incorporated by
reference therein.
6. ☐ Microfiche Computer Program (Appendix)
7. ☐ Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
a. ☐ Computer Readable Copy
b. ☐ Paper Copy (identical to computer copy)
c. ☐ Statement verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

8. ☒ Power of Attorney
9. ☒ Information Disclosure Statement (IDS)/Cover Letter plus PTO-1449 ☒ Copies of IDS Citations
10. ☐ Preliminary Amendment
11. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
12. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
13. ☐ Other:

14. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior Application No.: ____/____

15. ☒ **DELETION OF INVENTOR(S) STATEMENT:** This application is being filed by less than all the inventors named in the prior application. In accordance with 37 CFR 1.63(d)(2) and 1.33(b), the Assistant Commissioner is requested to delete the name(s) of the following person or persons who are not inventors of the invention being claimed in this application:

Jay S. Tourigny

16. ☐ Amend the specification by inserting before the first line the sentence:
-- This is a ☐ continuation-in-part, ☐ continuation, ☐ division of Application No. ____
, now abandoned. --
17. ☐ Cancel in this application original claims ____ of the prior application before calculating the filing. (At least one original independent claim must be retained for filing purposes.)
18. ☐ Priority of foreign Application No. ____ filed on ____ in ____ is
claimed under 35 U.S.C. 119.

CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	16 - 20 =	0	x \$ 18 =	0
	INDEPENDENT CLAIMS (37 CFR 1.16(b))	1 - 3 =	0	x \$ 78 =	0
	MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$ 260 =	260.00
				BASIC FEE (37 CFR 1.16(a))	+ \$ 760.00
				TOTAL =	\$ 1020.00

19. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 04-1928:

a. ☒ Fees required under 37 CFR 1.16.


b. ☒ Fees required under 37 CFR 1.17.

20. ☐ Other:

21. CORRESPONDENCE ADDRESS

NAME	Mark A. Edwards				
ADDRESS	E. I. du Pont de Nemours and Company				
	Legal - Patents				
	1007 Market Street				
CITY	Wilmington	STATE	Delaware	ZIP CODE	19898
COUNTRY	U.S.A.	TELEPHONE	302-992-5909	FAX	302-892-0699

22. SIGNATURE OF ATTORNEY OR AGENT REQUIRED

NAME	Mark A. Edwards	REG. NO.: 39,542
SIGNATURE		
DATE	9/17/99	

TITLE

NON-FLAMMABLE, HIGH-SOLVENCY COMPOSITIONS
COMPRISING TRANS-1,2-DICHLOROETHYLENE, SOLVENT, AND
INERTING AGENT

5

CROSS REFERENCE TO RELATED APPLICATIONS

This application claims the priority benefit of
U.S. Provisional Patent Application 60/101182, filed
September 21, 1998.

10

FIELD OF THE INVENTION

The present invention relates to non-flammable,
high-solvency compositions comprising trans-1,2-
dichloroethylene, oxygen-containing and/or hydrocarbon
solvent, and fluorocarbon inerting agent. The
compositions have utility as cleaning agents in the
electronics and refrigeration industries, and as a
medium for mold release agents.

20

BACKGROUND

It is well known that trans-1,2-dichloroethylene, a
flammable cleaning agent, has fair solvency with a wide
variety of difficult soils found in the electronics and
refrigeration industries. It is further known that
mixtures of trans-1,2-dichloroethylene and halocarbons
have utility in cleaning applications. For example,
trans-1,2-dichloroethylene blended with
chlorofluorocarbon ("CFC")-113 ($\text{CF}_2\text{ClCFCl}_2$) in
compositions formerly known as Freon® MCA and Freon®
SMT. In the late 1980's, it was postulated that
chlorofluorocarbons posed the risk of potential
environmental problems (i.e. stratospheric ozone
depletion and global warming). Notably, CFC-113 is an
alleged depletor of stratospheric ozone. In view of
the potential environmental problems associated with
stratospheric ozone depletion, the above Freon®
products were considered transitional materials
possessing properties that make them useful substitutes

for chlorofluorocarbons, while research for CFC-substitutes was conducted.

Additionally, trans-1,2-dichloroethylene has been reported to form azeotropes and azeotrope-like compositions with fluorocarbons and other solvents, as well as with 1,1,1,2,3,4,4,5,5,5-decafluoropentane, and alcohols, such as methanol and ethanol. However, the cleaning ability of these azeotrope-like compositions is compromised due to the minor amounts of trans-1,2-dichloroethylene and alcohol present.

Accordingly, users of industrial cleaning agents are faced with the dilemma: how does one find an environmentally acceptable alternative that retains non-flammability without sacrificing cleaning power? Highly fluorinated solvents meet the environmental and safety requirements, yet they are relatively weak solvents.

The present invention is advantageous in that it provides cleaning agents that are non-ozone depleting, low in global warming, non-flammable, and do not sacrifice cleaning power. Another advantage of the invention is that it departs from the paradigm that necessitates the use of azeotropes, wherein the evaporation rate of all components is essentially the same through the use of phased evaporation of the flammable and inerting components. The compositions of the present invention are useful in cleaning printed circuit cards or flushing oil and particles from refrigeration or air conditioning systems. Another advantage of the present invention is the process of depositing mold release agent on the surface of a mold.

For the foregoing reasons there is a need for cleaning agents that are non-ozone depleting, low in global warming, non-flammable, and do not sacrifice cleaning power. These and other features, aspects, and advantages of the present invention will become more apparent with reference to the following Summary, Description and appended claims.

SUMMARY

The present invention is directed to compositions that satisfy the aforesaid need. The invention comprises non-flammable, high-solvency compositions comprising trans-1,2-dichloroethylene, oxygen-containing and/or hydrocarbon solvent, and a fluorinated inerting agent. These inventive compositions are non-flammable by Flame Extension Test ASTM D-3065 and Flash Point-Tag Closed Cup Test ASTM D-56-82, and have a Kauri Butanol value of at least about 40 by ASTM 1133-94.

According to an embodiment of the present invention, a composition is provided which comprises the components:

- a.) trans-1,2-dichloroethylene; and
- b.) at least one solvent selected from:
 - i.) oxygen-containing solvents selected from alcohols, ketones, esters, siloxanes, and ethers; and
 - ii.) hydrocarbon solvents represented by C_tH_{2t+2} or C_tH_{2t} , wherein t is from 4 to 12; and
- c.) at least one inerting agent selected from:
 - i.) hydrofluorocarbon inerting agents represented by the formula $C_xH_yF_{(2x+2-y)}$, wherein x is from 3 to 8, y is from 1 to 4, the mole ratio of F/H in the hydrofluorocarbon inerting agent is greater than 1.6, and wherein when the inerting agent is hydrofluorocarbon, the weight ratio of hydrofluorocarbon inerting agent to solvent is at least about 1.5; and
 - ii.) hydrofluorocarbon ether inerting agents represented by the formula $CrF_{2r+1}OC_sH_{2s+1}$, wherein r and s are independently selected from 1 to 6, r is greater than or equal to $2s$, and wherein when the inerting agent is

hydrofluorocarbon ether the weight ratio of hydrofluorocarbon ether inerting agent to solvent is at least about 3; and

iii.) hydrochlorofluorocarbon
5 inerting agents represented by the formulae $C_2HCl_2F_3$, C_2HClF_4 , and $C_3HCl_2F_5$, and wherein when the inerting agent is hydrochlorofluorocarbon the weight ratio of hydrochlorofluorocarbon inerting agent to solvent is at least about 2.

10 According to another embodiment of the present invention, a process for removing residue from a surface is provided, which comprises: (a) contacting a surface with the above composition; and (b) recovering the surface substantially free of residue.

15 According to another embodiment of the present invention, a process for depositing mold release agent on the surface of a mold is provided, which comprises: (a) contacting the surface of the mold with the above composition; and (b) evaporating the
20 components of said composition, with the exception of the mold release agent from the surface of the mold.

The present inventive compositions are non-ozone depleting alternatives to conventional chlorofluorocarbon and transitional
25 hydrochlorofluorocarbon compositions, comprising chlorofluorocarbons, such as CFC-113 (CF_2ClCCl_2F), and hydrochlorofluorocarbons, such as HCFC-141b (CCl_2FCH_3), used for vapor and liquid phase cleaning. The present inventive compositions contain major amounts of trans-
30 1,2-dichloroethylene and oxygen-containing or hydrocarbon solvent, and thus offer superior cleaning ability, while containing minor amounts of fluorinated inerting agents, which suprisingly render the present compositions non-flammable.

35

DETAILED DESCRIPTION

According to the present invention, the foregoing and other aspects, features, and advantages are attained by a composition comprising:

- a.) trans-1,2-dichloroethylene; and
- 5 b.) at least one solvent selected from:
 - i.) oxygen-containing solvents selected from alcohols, ketones, esters, siloxanes, and ethers; and
 - ii.) hydrocarbon solvents
 - 10 represented by C_tH_{2t+2} or C_tH_{2t} , wherein t is from 4 to 12; and
 - c.) at least one inerting agent selected from:
 - i.) hydrofluorocarbon inerting
 - 15 agents represented by the formula $C_xH_yF_{(2x+2-y)}$, wherein x is from 3 to 8, y is from 1 to 4, the mole ratio of F/H in the hydrofluorocarbon inerting agent is greater than 1.6, and wherein when the inerting agent is hydrofluorocarbon, the weight ratio of
 - 20 hydrofluorocarbon inerting agent to solvent is at least about 1.5; and
 - ii.) hydrofluorocarbon ether inerting agents represented by the formula $C_rF_{2r+1}OC_sH_{2s+1}$, wherein r and s are independently
 - 25 selected from 1 to 6, r is greater than or equal to 2s, and wherein when the inerting agent is hydrofluorocarbon ether the weight ratio of hydrofluorocarbon ether inerting agent to solvent is at least about 3; and
 - iii.) hydrochlorofluorocarbon
 - 30 inerting agents represented by the formulae $C_2HCl_2F_3$, C_2HClF_4 , and $C_3HCl_2F_5$, and wherein when the inerting agent is hydrochlorofluorocarbon the weight ratio of hydrochlorofluorocarbon inerting agent to solvent is at
 - 35 least about 2. It is required that the above compositions are non-flammable by Flame Extension Test ASTM D-3065 and Flash Point-Tag Closed Cup Test ASTM D-

56-82, and have a Kauri Butanol value of at least about 40 by ASTM 1133-94.

Oxygen-containing solvents of the present invention comprise hydrocarbon alcohols, ketones, esters, siloxanes, and ethers. Representative alcohols are those having a normal boiling point greater than about 60°C and less than about 120°C and represented by the formula $C_uH_{2u+1}OH$, wherein u is from 1 to 4. Such alcohols include methanol, ethanol, n-propanol, isopropanol, and n-butanol. Representative ketones are those having a normal boiling point greater than about 50°C and less than about 110°C and represented by the formula $C_vH_{2v+1}COC_wH_{2w+1}$, wherein v and w are 1 or greater and v+w is at most 5. Such ketones include the hydrocarbon ketones, propanone and butanone. Representative esters are those having a normal boiling point greater than about 55°C and less than about 130°C and represented by the formula $C_kH_{2k+1}COOC_mH_{2m+1}$, wherein k and m are 1 or greater and k+m is at most 4. Such esters include the hydrocarbon esters, ethyl acetate and propyl acetate. Representative siloxanes include the hydrocarbon siloxanes, hexamethyldisiloxane ($[(CH_3)_3Si]_2O$), hexaethyldisiloxane ($[(C_2H_5)_3Si]_2O$), and octamethyltrisiloxane ($(CH_3)_3SiOSi(CH_3)_2OSi(CH_3)_3$). Representative ethers include the ethylene glycol dialkyl ethers of formula $C_aH_{2a+1}(OCH_2CH_2)_bOC_aH_{2a+1}$, wherein a is 1 to 3 and b is 1 to 6. Such ethers include bis(2-methoxyethyl) ether.

Hydrocarbon solvents of the present invention are those having a normal boiling point greater than about -15°C and less than about 130°C, and represented by the formulae C_tH_{2t+2} or C_tH_{2t} , wherein t is from 4 to 8. Representative hydrocarbon solvents include butane, pentane, hexane, heptane, octane, and their structural isomers such as cyclopentane, methylcyclopentane, and cyclohexane. With regard to the cleaning processes disclosed herein, when the present composition is

delivered to the surface via aerosol, it preferred that that t is from 5 to 8.

Hydrofluorocarbon inerting agents of the present invention comprise hydrofluorocarbons represented by the general formula $C_xH_yF_{(2x+2-y)}$, wherein x is from 3 to 8, y is from 1 to 4, and the mole ratio of F/H in the individual hydrofluorocarbon inerting agent molecules is greater than 1.6. Representative hydrofluorocarbon inerting agents include: CF₃CHF₂CF₃ (HFC-227ea), CF₃CF₂CF₂H (HFC-227ca), CF₃CH₂CF₃ (HFC-236fa), CF₃CHF₂CF₂H (HFC-236ea), CF₂HCF₂CF₂H (HFC-236ca), CF₃CF₂CFH₂ (HFC-236cb), CH₂FCF₂CHF₂ (HFC-245ca), CHF₂CHFCHF₂ (HFC-245ea), CH₂FCHF₂CF₃ (HFC-245eb), CHF₂CH₂CF₃ (HFC-245fa), CF₃CF₂CF₂CF₂H (HFC-329p), CF₃CF₂CFHCF₃ (HFC-329me), CF₃CF₂CF₂CFH₂ (HFC-338q), CF₃CF₂CH₂CF₃ (HFC-338mf), CF₃CF₂CFHCF₂H (HFC-338pe), CF₃CFHCF₂CF₂H (HFC-338pce), CHF₂CF₂CF₂CF₂H (HFC-338pcc), CF₃CFHCFHCF₃ (HFC-338mee), CF₃CF₂CF₂CF₂CF₂H (HFC-42-11p), CF₃CF₂CFHCF₂CF₃ (HFC-42-11mce), CF₃CF₂CF₂CFHCF₃ (HFC-42-11me), CF₃CF₂CH₂CF₂CF₃ (HFC-43-10mcf), CF₃CF₂CF₂CH₂CF₃ (HFC-43-10mf), CF₃CF₂CF₂CF₂CFH₂ (HFC-43-10q), CF₃CF₂CF₂CFHCF₂H (HFC-43-10pe), CF₃CF₂CFHCF₂CF₂H (HFC-43-10pce), CF₃CHFCH₂CF₂CF₃ (HFC-43-10mee), CF₂HCF₂CF₂CF₂CF₂H (HFC-43-10pccc), CF₃CFHCF₂CF₂CF₂H (HFC-43-10pcce), CF₃CFHCF₂CFHCF₃ (HFC-43-10mece), and CF₃CF₂CF₂CF₂CF₂CF₂H (HFC-52-13p). Preferred of the hydrofluorocarbon inerting agents are CF₃CH₂CF₃ (HFC-236fa), CF₃CHF₂CF₃ (HFC-227ea), CHF₂CF₂CF₂CF₂H (HFC-338pcc), and CF₃CHFCH₂CF₂CF₃ (HFC-43-10mee).

Hydrofluorocarbon ether inerting agents of the present invention comprise hydrofluorocarbon ethers represented by the general formula $C_rF_{2r+1}OC_sH_{2s+1}$, wherein r and s are independently selected from 1 to 6 and r is greater than or equal to 2s. Representative hydrofluorocarbon ether inerting agents include C₄F₉OCH₃ and C₄F₉OC₂H₅.

Hydrochlorofluorocarbon inerting agents of the present invention comprise hydrochlorofluorocarbons

represented by the formula $C_2HCl_2F_3$, C_2HClF_4 , and $C_3HCl_2F_5$. Representative hydrochlorofluorocarbon inerting agents include: $CHCl_2CF_3$ (HCFC-123), $CHClFCF_2Cl$ (HCFC-123a), CCl_2FCHF_2 (HCFC-123b), $CHClFCF_3$ (HCFC-124), $CClF_2CF_2H$ (HCFC-124a), $CHF_2CCl_2CF_3$ (HCFC-225aa), $CHClFCClFCF_3$ (HCFC-225ba), $CHF_2CClFCClF_2$ (HCFC-225bb), $CHCl_2CF_2CF_3$ (HCFC-225ca), $CHClFCF_2CClF_2$ (HCFC-225cb), $CHF_2CF_2CCl_2F$ (HCFC-225cc), $CClF_2CHClCF_3$ (HCFC-225da), $CClF_2CHFCClF_2$ (HCFC-225ea), and $CF_3CHFCCl_2F$ (HCFC-225eb). Preferred of the hydrochlorofluorocarbon inerting agents are $CHCl_2CF_3$ (HCFC-123), $CHClFCF_3$ (HCFC-124), $CHCl_2CF_2CF_3$ (HCFC-225ca), and $CHClFCF_2CClF_2$ (HCFC-225cb).

The present composition comprises from about 40 to about 80 weight% of trans-1,2-dichloroethylene, from about 20 to about 45 weight% inerting agent, and about 15 weight% or less of solvent. Preferably, the compositions comprises from about 55 to about 75 weight% of trans-1,2-dichloroethylene, from about 20 to about 45 weight% inerting agent, and about 15 weight% or less of solvent. When the inerting agent comprises hydrofluorocarbon, the weight ratio of hydrofluorocarbon to solvent is at least about 1.5. When the inerting agent comprises hydrofluorocarbon ether, the weight ratio of hydrofluorocarbon ether to solvent is at least about 3. When the inerting agent comprises hydrochlorofluorocarbon, the weight ratio of hydrochlorofluorocarbon to solvent is at least about 2.

In an embodiment of the present invention when a composition contains more than one species of inerting agent (i.e., at least one compound selected from the group consisting of hydrofluorocarbon, hydrofluorocarbon ether, and hydrochlorofluorocarbon inerting agent species) the total amount of inerting agent required will be a weighted sum of the weights of individual inerting agent species; weighted by the ratio of inerting agent to solvent required for each inerting agent species. In other words, when a present

composition contains more than one species of inerting agent, the present composition will obey the expression: $W^S = W^{HFC}/1.5 + W^{HFE}/3 + W^{HCFC}/2$, wherein W^S , W^{HFC} , W^{HFE} , W^{HCFC} represent the weights of solvent, 5 hydrofluorocarbon inerting agent, hydrofluorocarbon ether inerting agent, and hydrochlorofluorocarbon inerting agent, respectively, in the present composition.

The present compositions contain an inerting amount of inerting agent. By inerting amount is meant 10 an amount of inerting agent which is sufficient to render the composition (i.e., mixture comprising trans-1,2-dichloroethylene, inerting agent, solvent, and other optional components such as aerosol propellant) 15 non-flammable by the following two tests: Flame Extension Test (ASTM D-3065) and Flash Point - Tag Closed Cup Test (ASTM D-56-82). Both of the aforementioned ASTM test methods are herein incorporated by reference.

20 Present composition components are selected such that an inerting amount of inerting agent is maintained together with trans-1,2-dichloroethylene and solvent during delivery to the surface (e.g., as an aerosol, vapor, or liquid phase), after deposition on, 25 and during evaporation from a surface. Appropriate selection assures that the evaporation rate of solvent and inerting agent from a surface is similar enough such that neither a flammable vapor nor liquid phase of solvent may form as the present composition evaporates 30 from a surface. A multitude of variables affect evaporation rate and a quantitative relationship between these variables and evaporation rate of a compound is complex. However, the following equation allows for qualitative comparison of compounds at a 35 given temperature: $R = 0.8217 \times P \times (MW)^{1/2}$, wherein R is defined as the evaporation index, P is the vapor pressure of the compound in mmHg at a given temperature, and MW is the molecular weight of the

compound (see, Stratta, J. John; Dillon, Paul W.; and Semp, Robert H. in "Evaporation of organic cosolvents from water-borne formulations. Theory, experimental study, computer simulation", in J. Coat. Technol.

- 5 (1978), 50(647), pages 39-47). The evaporation index is a relative measurement based on n-butyl acetate, wherein n-butyl acetate's evaporation index is set to 100. Exemplary evaporation indexes are provided for selected compounds in Table 1 below.

10

TABLE 1 - Evaporation Index at 25°C for Selected Compounds

COMPOUND	Evaporation Index
trans-1,2-dichloroethylene	2,654
<i>INERTING AGENT</i>	
HFC-227ea (CF ₃ CFHCF ₃)	38,773
HFC-236fa (CF ₃ CH ₂ CF ₃)	20,697
HFC-245fa (CF ₃ CH ₂ CF ₂ H)	10,411
HCFC-225ca/cb 45/55 Wt% (CHCl ₂ CF ₂ CF ₃ /CHClFCFC ₂ CClF ₂)	3,395
HFC-43-10mee (CF ₃ CFHCFHCF ₂ CF ₃)	2,948
HFE-7100 (CH ₃ OC ₄ F ₉)	2,624
<i>SOLVENT</i>	
Butane	11,408
Pentane	3,632
propanone (acetone)	1,543
Ethanol	328
iso-propanol	280

- 15 In a preferred embodiment of the present invention, inerting agent and solvent are chosen such that the ratio of inerting agent/solvent evaporation indexes is from about 0.1 to about 100. More preferably, such ratio of evaporation indexes will be

from about 0.5 to about 20, and most preferably, from about 5 to 10.

The present composition contains an effective amount of non-inerting agent components (i.e., trans-1,2-dichloroethylene and solvent). In one sense, an effective amount of non-inerting agent components is defined as an amount which is sufficient to remove at least some undesirable residue from a residue-containing surface, preferably, substantially all residue from the surface. By substantially all residue from the surface or a residue-free surface, is meant that the amount of residue remaining following contact of the surface with the present composition is either undetectable by the senses (e.g. visual: the naked eye or low magnification (10x or less)) and conventional analytical methodology used to detect the residue (e.g., Omega brand surface ionic residue meter), or the amount of residue remaining on the surface after contact with the present composition has no consequence on further use of, or further processes carried out on, the surface.

An effective amount of non-inerting agent components in the present composition which removes substantially all residue from a surface to form a substantially residue-free surface may be further defined as an amount of non-inerting agent components which results in the present composition having a Kauri-Butanol value (Kb) of at least about 40, preferably about 100, when determined by ASTM D-1133-94. The aforementioned ASTM D-1133-9 test method is herein incorporated by reference. The Kb value reflects the ability of a composition to solubilize various organic residues (e.g, machine and conventional refrigeration lubricants).

An effective amount of non-inerting agent components in the present composition which removes substantially all residue from a surface to form a residue-free surface may be defined as an amount of

such components which removes ionic residue from a surface to about 14.0 micrograms per square inch or less and leaves the surface substantially free of visible residue (i.e., no residue evident to the naked eye or up to 10X magnification). Common articles of manufacture containing ionic contamination which require precision cleaning are integrated circuit devices manufactured in part by a soldering process. It is critical to ensure cleanliness of surfaces to be connected prior to soldering. This is accomplished by using a temperature-activated rosin flux. The flux removes oxides and other contamination from the surfaces to be joined. After soldering, flux residues are preferably cleaned to about 14.0 micrograms per square inch or less to avoid failure of the integrated circuit device.

Another embodiment of the present composition comprises aerosol propellant. Aerosol propellant may assist in delivering the present composition from a storage container to a surface in the form of an aerosol. Aerosol propellant is optionally included in the present composition in up to about 25 weight percent of the total composition. Representative aerosol propellants comprise air, nitrogen, carbon dioxide, difluoromethane (CF_2H_2 , HFC-32), trifluoromethane (CF_3H , HFC-23), difluoroethane (CHF_2CH_3 , HFC-152a), trifluoroethane (CH_3CF_3 , HFC-143a; $\text{CHF}_2\text{CH}_2\text{F}$, HFC-143), tetrafluoroethane ($\text{CF}_3\text{CH}_2\text{F}$, HFC-134a; $\text{CF}_2\text{HCF}_2\text{H}$, HFC-134), and pentafluoroethane ($\text{CF}_3\text{CF}_2\text{H}$, HFC-125).

Another embodiment of the present invention further includes processes for removing residue from a surface, comprising the steps of:

contacting the surface with the present composition, and recovering the surface substantially residue-free.

In one embodiment of the aforesaid processes, the surface comprises an integrated circuit device, the residue comprises soldering flux or oil, and the device is recovered substantially free of flux and oil following said contacting step. The method of contacting is not critical, and may occur by submersing the surface in the present composition or wiping the surface with the present composition. Preferably in this embodiment, the present composition further comprises aerosol propellant and the present composition is delivered to the surface during said contacting step as an aerosol.

In another embodiment of the aforementioned processes, the surface comprises the interior surface of a compression refrigeration apparatus, the residue comprises refrigerant, compressor lubricant (e.g., mineral oil, naphthenes, polyol ethers), particulates, and rust, and the inner surface of the compression refrigeration apparatus is recovered substantially free of residue following said contacting step. The method of contacting is not critical. Contacting may occur by flushing present composition in a liquid phase through a refrigeration apparatus. Present composition further comprising aerosol propellant is desirable in this embodiment, as the vapor pressure of the aerosol propellant may be used to move present composition throughout a refrigeration apparatus.

Another embodiment of the present invention includes mold release compositions and processes for depositing mold release agent on the interior surface of a mold. Polymer (e.g., thermolastic, thermoset, elastomer, rubber) articles may be manufactured by hot molding. A mold release agent is typically applied to the interior surface of the mold prior to polymer molding to reduce or negate the attractions between the mold surface and polymer. Mold release agent allows for facile release and recovery of a molded polymer article from a mold. Mold release agents used depend

on the polymer being molded but are generally polymeric silicon-based organic compounds (e.g., silicones, siloxanes) or fluorinated organic polymers (e.g., tetrafluoroethylene homopolymer, or copolymers with other fluorinated and partially halogenated monomers) and are typically solid or viscous and tacky liquids at standard temperature. Such mold release agents are generally delivered to the interior surface of a mold as a solution or dispersion in a solvent which allows for ease in handling and homogenous distribution of a thin coating of mold release agent on the mold's surface. Mold release agent may be dissolved or dispersed in the present composition resulting in formation of a mold release composition. The present inventive mold release composition, containing an inerting amount of inerting agent, is non-flammable. Further, the inerting agent present in the mold release composition serves to dilute the concentration of trans-1,2-dichloroethylene and solvent which contacts the mold surface and polymers, thus compatibilizing the mold release composition with polymers and mold release surface which can be adversely affected by trans-1,2-dichloroethylene and solvent. This compatibilizing effect of the present inerting agent results in less hazing and swelling of polymeric mold components, surfaces, and connections. The present invention thus includes the present composition further comprising mold release agent for delivering and homogenously dispersing mold release agent upon the interior surface of a mold. The present composition further comprising dissolved or dispersed mold release agent may be applied as a liquid or aerosol composition to the surface of a mold. The present invention further includes processes for depositing mold release agent on the interior surface of a mold, comprising contacting the surface of the mold with the present composition further comprising mold release agent, and evaporating the components of the composition other than mold

release agent, thereby depositing mold release agent on the surface of the mold.

EXAMPLES

5 In the following examples, "Trans" refers to trans-1,2-dichloroethylene, "HCFC-225" refers to a mixture being 55-58 wt% HCFC-225ca ($\text{CF}_3\text{CF}_2\text{CHCl}_2$) and 42-45 wt% HCFC-225cb ($\text{CF}_2\text{ClCF}_2\text{CHClF}$), and "HCFC-141b" refers to CCl_2FCH_3 .

10

FLAMMABILITY TESTING

The present composition, when delivered as an aerosol, has a flame extension not greater than 18" and a flash back of not greater than 6" per test method
15 ASTM D-3065. This test method involves holding an aerosol can containing a composition for testing 6" from a lit plumbers candle and spraying it through a 2-3" flame and observing the length of flame extension back to the aerosol can with the the can's valve fully
20 open. Flash back length is defined as the length the flame goes back from the candle back to the aerosol can. Candidate compositions were tested to find the minimum concentration of the inerting agent required to yield flame extension less than 18" and flash back of
25 less than 6". Additionally, the present composition does not have a closed cup flash point per ASTM D-56-82. Results are described in Table 1.

Table 1 - Aerosol Flammability Testing (per ASTM
30 D-3065)

Compositions were put in an aerosol can with 20% propellant (HFC-134a) All compositions are reported in weight% of components.

-Flame Extension >18" classifies an aerosol can as
35 FLAMMABLE by DOT
-Flash Back >6" classifies an aerosol can as
EXTREMELY
FLAMMABLE by DOT

- "Flame" notes inches of flame extension
- "Flash Back" notes any flame propagation back to aerosol can
- "Flsh Pt" is Flash Point by Tag Closed Cup (ASTM

5 D-56-

82)

Component	Weight% of Component in Composition											
HFC-43-10mee	4	0	0	4	4	4						
Trans	6	5	0	3	0	3	0	3	1	5	3	8
Ethanol	0	5	0			3		3	3	3	3	3
Methanol												
C ₄ F ₉ OCH ₃							4	4	6	2		
HCFC-225											4	9
HCFC-141b												5
Flame	8+	8+	8+	0	0			8+	8+	0	8+	0
Flashback	0	0	0	0	0	0	0	0	0	0	0	0
Flash Point					0	0	0			0		0

Table 1 Summary: Minimum amount of inerting agent required for present aerosol composition to have less than 18" of flame extension:

	Weight% Components In Composition (& Excluding Propellant)		
HFC-43-10mee	19 (24)	-	-
C ₄ F ₉ OCH ₃	-	34 (42)	-
HCFC-225	-	-	24 (29)
Trans	51 (63)	36 (45)	46 (58)
Ethanol	10 (13)	10 (13)	10 (13)
Propellant (HFC-134a)	20	20	20

Cleaning Performance Testing

In a preferred sense, the present composition cleans ionic contamination (flux residue) from a surface to about 14.0 micrograms or less per square inch of surface area and leaves the surface substantially free of visible residue to the naked eye. The test used to determine surface cleanliness involved the following steps:

1. Kester 185 RMA rosin flux is painted liberally onto a FR-4 test board (an epoxy printed wiring board with tracing made of tinned copper),
2. The board so treated is then heated in an oven at 175°C for 2 minutes to activate the rosin flux,
3. The board is then immersed in solder (Sn63, a 63/37 Sn/Lead solder) at 204°C for 10 seconds,
4. The board is then cleaned (at room temperature) for 1 minute by immersing in present composition and providing gentle movement of the board,
5. The board is then visually inspected and tested (in triplicate) for residual ionics with an Omega Meter 600 SMD ionic analyzer.

PERFORMANCE TESTING: BLENDS TESTED

Blend #	HFC-43-10mee	C ₄ F ₉ OCH ₃	HCFC-225	HCFC-141b	Trans	Ethanol	Methanol
#1	24	-	-	-	70	6	-
#2	24	-	-	-	63	13	-
#3	51	-	-	-	43	-	6
#4	-	42	-	-	45	13	-
#5	-	-	-	95	-	-	5
#6	-	-	29	-	58	13	-

Acceptance Criteria: Residual ionics below 14.0 micrograms per square inch and surface substantially free of residue.

Flux Test (Blend #)	Visual Inspection	Residual Ionics ($\mu\text{g NaCl/in}^2$)
#1	very light residue	9.8, 6.9, 6.6 (7.8 avg)
#2	no visible residue	8.1, 7.9, 6.0 (7.3 avg)
#3	very light residue	7.4, 7.0, 9.7 (8.0 avg)
#4	very light residue	9.9, 7.6, 6.3 (7.9 avg)
#5	very light residue	6.1, 7.5, 9.6 (7.7 avg)
#6	No visible residue	5.0, 5.0, 4.7 (4.9 avg)

SOLVENCY POWER

5 A measure of "solvency power" - the ability
 of a solvent to dissolve an organic residue -- is the
 Kauri-Butanol value (Kb) determined by ASTM 1133-94.
 Compositions of the present invention have a Kb of at
 least about 40, preferably at least about 50. In the
 present context, ASTM 113-94 comprises taking 10 grams
 10 of present composition and adding an oil/grease/fluid
 drop-wise until the solution becomes hazy and non-
 homogeneous, defining the solubility point or
 saturation point of that residue in the present
 composition. The data is reported in grams per 100
 15 gram of present composition or weight percent
 solubility.

TABLE 2: OIL SOLUBILITY AND Kb VALUE COMPARISON

Oil	Blend #				
	2	3	4	6	n-propyl bromide
AM Drawing 2000	5.5	3.4	4.2	6.0	5.6
Hardcut 541	30.4	8.4	25.0	33	32.4
Houghton Rust Veto 76- mb	43.8	26.3	36.1	40	42.5
Mil-H-5606G Hydraulic Fluid	22.8	14.8	16.9	20.8	23
Tapmatic Cutting Fluid	50.6	25	40	40	45.4
Kb Value (ASTM D-1133- 94)	110	33	46	> 140	125

SOLUBILITY TESTS WITH HVAC LUBRICANTS

5

To establish the effectiveness of the present compositions in cleaning compression refrigeration apparatus, the solubility at room temperature of two refrigeration oils was examined in present composition as well as comparative materials, e.g., HCFC-141b (CFCl₂CH₃), the refrigeration industry standard in compression refrigeration system cleaning. The "mineral oil" lubricant tested was Carquest part no. 209500, "refrigeration Oil for R12 Air conditioning Systems". The PAG (polyalkylene glycol) oil tested was Pyroil PAG RL 488, "High Viscosity Oil for HFC-134a A/C System". All percentages reported are in weight percent of the total composition.

10

15

Composition Tested	Mineral Oil Solubility	PAG Oil Solubility
HCFC-141b	yes, completely soluble	yes, completely soluble
C5 HFC	no, 2 phases	partial,

	formed	after stirring
C3 HFC	no, 2 phases formed	partial, after stirring
C4 HFC	no, 2 phases formed	partial, after stirring
67% HFC C5, 33% trans	partial, after stirring	yes, completely soluble
96% C3 HFC, 4 wt% C ₅ H ₁₂ or C ₆ H ₁₄	no, 2 phases formed	partial, after stirring
50% C4 HFC, 35% C5 HFC, 15% trans	no, 2 phases formed	yes, completely soluble
66% C5 HFC, 30% trans, 4% methanol	no, 2 phases formed	yes, completely soluble
24% C5 HFC, 64% trans, 12% ethanol	yes, completely soluble	yes, completely soluble
HFE based solvent	no, 2 phases formed	partial, after stirring
33% C5 HFC, 33% C4 HFC, 33% trans	no, 2 phases formed	yes, completely soluble
20% C5 HFC, 40% C4 HFC, 40% trans	partial, after stirring	yes, completely soluble
15% C5 HFC, 30% C4 HFC, 15% C3 HFC, 40% trans	no, 2 phases formed	no, 2 phases formed
30% C5 HFC, 26% C4 HFC, 40% trans, 4% methanol	partial, after stirring	Yes, completely soluble
25% C5 HFC, 30% C4 HFC, 45% trans	cloudy, partially soluble after stirring	N/A
25% C5 HFC, 30% C4 HFC, 45% n-	no, very cloudy	N/A

propyl bromide		
31% C5 HFC, 29% C4 HFC, 50% trans	yes, completely soluble	yes, completely soluble

WHAT IS CLAIMED IS:

1. A composition comprising:
 - a.) trans-1,2-dichloroethylene; and
 - 5 b.) at least one solvent selected from the group consisting of:
 - i.) oxygen-containing solvents selected from the group consisting of alcohols, ketones, esters, siloxanes, and ethers; and
 - 10 ii.) hydrocarbon solvents selected from the group consisting of those represented by C_tH_{2t+2} and C_tH_{2t} , wherein t is from 4 to 12; and
 - c.) at least one inerting agent selected from the group consisting of:
 - 15 i.) hydrofluorocarbon inerting agents selected from the group consisting of those represented by the formula $C_xH_yF_{(2x+2-y)}$, wherein x is from 3 to 8, y is from 1 to 4, the mole ratio of F/H in the hydrofluorocarbon inerting agent is greater than 1.6, and wherein when the inerting agent is hydrofluorocarbon the weight ratio of hydrofluorocarbon inerting agent to solvent is at least about 1.5;
 - 20 ii.) hydrofluorocarbon ether inerting agents selected from the group consisting of those represented by the formula $C_rF_{2r+1}OC_sH_{2s+1}$, wherein r and s are independently selected from 1 to 6, r is greater than or equal to 2s, and wherein when the inerting agent is hydrofluorocarbon ether the weight ratio of hydrofluorocarbon ether inerting agent to solvent is at least about 3; and
 - 25 iii.) hydrochlorofluorocarbon inerting agents selected from the group consisting of those represented by the formulae $C_2HCl_2F_3$, C_2HClF_4 , and $C_3HCl_2F_5$, and wherein when the inerting agent is hydrochlorofluorocarbon the weight ratio of hydrochlorofluorocarbon inerting agent to solvent is at least about 2,
 - 30
 - 35

wherein said composition is non-flammable by Flame Extension Test ASTM D-3065 and Flash Point-Tag Closed Cup Test ASTM D-56-82, and said composition has a Kauri Butanol value of at least about 40 by ASTM 1133-94.

2. The composition of Claim 1, wherein said composition has a Kauri Butanol value of at least about 100 by ASTM 1133-94.

3. The composition of Claims 1 or 2, wherein the ratio of (inerting agent evaporation index)/(solvent evaporation index) is from about 0.1 to about 100.

4. The composition of Claims 1 or 2 wherein said oxygen-containing solvent is selected from the group consisting of alcohols having a normal boiling point greater than about 60°C and less than about 120°C, and represented by the formula $C_uH_{2u+1}OH$, wherein u is from 1 to 4; ketones having a normal boiling point greater than about 50°C and less than about 110°C, and represented by the formula $C_vH_{2v+1}COC_wH_{2w+1}$, wherein v and w are 1 or greater and v+w is at most 5; esters having a normal boiling point greater than about 55°C and less than about 130°C, and represented by the formula $C_kH_{2k+1}COOC_mH_{2m+1}$, wherein k and m are 1 or greater and k+m is at most 4; siloxanes, hexamethyldisiloxane $[(CH_3)_3Si]_2O$, hexaethyldisiloxane $[(C_2H_5)_3Si]_2O$, and octamethyltrisiloxane $(CH_3)_3SiOSi(CH_3)_2OSi(CH_3)_3$; and ethylene glycol dialkyl ethers represented by the formula $C_aH_{2a+1}(OCH_2CH_2)_bOC_aH_{2a+1}$, wherein a is 1 to 3 and b is 1 to 6.

5. The composition of Claims 1 or 2 wherein said hydrocarbon solvent has a normal boiling point greater than about -15°C and less than about 130°C.

6. The composition of Claims 1 or 2 wherein said hydrofluorocarbon inerting agent is selected from the group consisting of $\text{CF}_3\text{CHF}_2\text{CF}_3$ (HFC-227ea), $\text{CF}_3\text{CF}_2\text{CF}_2\text{H}$ (HFC-227ca), $\text{CF}_3\text{CH}_2\text{CF}_3$ (HFC-236fa), $\text{CF}_3\text{CHF}_2\text{CF}_2\text{H}$ (HFC-236ea), $\text{CF}_2\text{HCF}_2\text{CF}_2\text{H}$ (HFC-236ca), $\text{CF}_3\text{CF}_2\text{CFH}_2$ (HFC-236cb), $\text{CH}_2\text{F}_2\text{CF}_2\text{CHF}_2$ (HFC-245ca), $\text{CHF}_2\text{CHF}_2\text{CHF}_2$ (HFC-245ea), $\text{CH}_2\text{FCH}_2\text{CF}_3$ (HFC-245eb), $\text{CHF}_2\text{CH}_2\text{CF}_3$ (HFC-245fa), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-329p), $\text{CF}_3\text{CF}_2\text{CFHCF}_3$ (HFC-329me), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CFH}_2$ (HFC-338q), $\text{CF}_3\text{CF}_2\text{CH}_2\text{CF}_3$ (HFC-338mf), $\text{CF}_3\text{CF}_2\text{CFHCF}_2\text{H}$ (HFC-338pe), $\text{CF}_3\text{CFHCF}_2\text{CF}_2\text{H}$ (HFC-338pce), $\text{CHF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-338pcc), $\text{CF}_3\text{CFHCFHCF}_3$ (HFC-338mee), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-42-11p), $\text{CF}_3\text{CF}_2\text{CFHCF}_2\text{CF}_3$ (HFC-42-11mce), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CFHCF}_3$ (HFC-42-11me), $\text{CF}_3\text{CF}_2\text{CH}_2\text{CF}_2\text{CF}_3$ (HFC-43-10mcf), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CH}_2\text{CF}_3$ (HFC-43-10mf), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{CFH}_2$ (HFC-43-10q), $\text{CF}_3\text{CF}_2\text{CF}_2\text{CFHCF}_2\text{H}$ (HFC-43-10pe), $\text{CF}_3\text{CF}_2\text{CFHCF}_2\text{CF}_2\text{H}$ (HFC-43-10pce), $\text{CF}_3\text{CHFCH}_2\text{CF}_2\text{CF}_3$ (HFC-43-10mee), $\text{CF}_2\text{HCF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-43-10pccc), $\text{CF}_3\text{CFHCF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-43-10pcce), $\text{CF}_3\text{CFHCF}_2\text{CFHCF}_3$ (HFC-43-10mece), and $\text{CF}_3\text{CF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{CF}_2\text{H}$ (HFC-52-13p).

7. The composition of Claims 1 or 2 wherein said hydrofluorocarbon ether inerting agent is selected from the group consisting of $\text{C}_4\text{F}_9\text{OCH}_3$ and $\text{C}_4\text{F}_9\text{OC}_2\text{H}_5$.

8. The composition of Claims 1 or 2 wherein said hydrochlorofluorocarbon inerting agent is selected from the group consisting of CHCl_2CF_3 (HCFC-123), $\text{CHCl}_2\text{CF}_2\text{Cl}$ (HCFC-123a), $\text{CCl}_2\text{FCH}_2\text{F}$ (HCFC-123b), CHCl_2CF_3 (HCFC-124), $\text{CCl}_2\text{F}_2\text{CF}_2\text{H}$ (HCFC-124a), $\text{CHF}_2\text{CCl}_2\text{CF}_3$ (HCFC-225aa), $\text{CHCl}_2\text{CFCl}_2\text{CF}_3$ (HCFC-225ba), $\text{CHF}_2\text{CCl}_2\text{CFCl}_2\text{F}$ (HCFC-225bb), $\text{CHCl}_2\text{CF}_2\text{CF}_3$ (HCFC-225ca), $\text{CHCl}_2\text{CF}_2\text{CCl}_2\text{F}$ (HCFC-225cb), $\text{CHF}_2\text{CF}_2\text{CCl}_2\text{F}$ (HCFC-225cc), $\text{CCl}_2\text{F}_2\text{CHCl}_2\text{CF}_3$ (HCFC-225da), $\text{CCl}_2\text{F}_2\text{CHFCCl}_2\text{F}$ (HCFC-225ea), and $\text{CF}_3\text{CHFCCl}_2\text{F}$ (HCFC-225eb).

9. The composition of Claims 1 or 2 wherein said inerting agent comprises $\text{CF}_3\text{CHFCH}_2\text{CF}_2\text{CF}_3$ (HFC-43-10mee), and said solvent comprises ethanol.

10. The composition of Claim 9 comprising about 63 weight% trans-1,2-dichloroethylene, about 13 weight% ethanol, and about 24 weight% $\text{CF}_3\text{CHFCHFCF}_2\text{CF}_3$ (HFC-43-10mee).

11. The composition of Claims 1 or 2 further comprising at least one aerosol propellant selected from the group consisting of air, nitrogen, carbon dioxide, difluoromethane, trifluoromethane, difluoroethane, trifluoroethane, and tetrafluoroethane.

12. A process for removing residue from a surface, comprising the steps of:

15 a.) contacting the surface with the composition of Claims 1, 2, 9, 10 or 11; and

b.) recovering the surface substantially free of residue.

13. The process of Claim 12, wherein the surface comprises an integrated circuit device, and the residue comprises soldering flux.

14. The process of Claim 12, wherein the surface comprises an interior surface of a compression refrigeration apparatus, and the residue comprises conventional refrigeration lubricant, particulates, and/or rust.

15. The composition of Claims 1, 2, 9, 10 or 11, further comprising a mold release agent.

16. A process for depositing mold release agent on the surface of a mold, comprising:

35 a.) contacting the surface of the mold with the composition of Claim 13; and

b.) evaporating the components of said composition, with the exception of the mold release agent, from the surface of the mold.

ABSTRACT OF THE DISCLOSURE

Disclosed are non-flammable, high-solvency compositions having utility as cleaning agents in the electronics and refrigeration industries, and as a medium for mold release agents. The compositions are non-flammable by Flame Extension Test ASTM D-3065 and Flash Point-Tag Closed Cup Test ASTM D-56-82, and have a Kauri Butanol value of at least about 40 by ASTM 1133-94. The compositions comprise the components: a.) trans-1,2-dichloroethylene; and b.) solvent selected from: i.) oxygen-containing solvents selected from alcohols, ketones, esters, siloxanes, and ethers; and ii.) hydrocarbon solvents represented by C_tH_{2t+2} or C_tH_{2t} , wherein t is from 4 to 8; and c.) an inerting agent selected from: i.) hydrofluorocarbon inerting agents represented by the formula $C_xH_yF_{(2x+2-y)}$, wherein x is from 3 to 8, y is from 1 to 4, and the mole ratio of F/H in the hydrofluorocarbon inerting agent is greater than 1.6; ii.) hydrofluorocarbon ether inerting agents represented by the formula $C_rF_{2r+1}OC_sH_{2s+1}$, wherein r and s are independently selected from 1 to 6, and r is greater than or equal to 2s; and iii.) hydrochlorofluorocarbon inerting agents represented by the formulae $C_2HCl_2F_3$, C_2HClF_4 , and $C_3HCl_2F_5$.

DECLARATION and POWER OF ATTORNEY

As a below-named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

NON-FLAMMABLE, HIGH-SOLVENCY COMPOSITIONS COMPRISING TRANS-1,2-DICHLOROETHYLENE, SOLVENT, AND INERTING AGENT

the specification of which is attached hereto unless the following box is checked:

☐ was filed on _____ as U.S. Application No. _____ or PCT International Application No. _____ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is known to me to be material to patentability as defined in 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Application No.	Country	Filing Date	Priority Claimed (Yes/No)
-----------------	---------	-------------	---------------------------

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States Provisional Application(s) listed below.

U.S. Provisional Application No.	U.S. Filing Date
60/101,182	09/21/98

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or § 365(c) of any PCT International Application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application or PCT International Application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is known to me to be material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

Application No.	Filing Date	Status (patented, pending or abandoned)
-----------------	-------------	---

POWER OF ATTORNEY: I hereby appoint the following attorney(s) and/or agent(s) the power to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

Name: MARK A. EDWARDS JAMES E. SHIPLEY	Registration No.: 39,542 32,003
Send correspondence and direct telephone calls to: MARK A. EDWARDS	E. I. du Pont de Nemours and Company Legal - Patents Wilmington, DE 19898, U.S.A. Tel. No. (302) 992-5909 Fax No. (302) 892-0699

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

INVENTOR(S)

Full Name of Inventor	Last Name WESTBROOK	First Name GREG	Middle Name A.
	Signature (please sign full name):		Date:
Residence & Citizenship	City PORT NECHES	State or Foreign Country TEXAS	Country of Citizenship U.S.A.
Post Office Address	Post Office Address 3155 CANTERBURY LANE	City PORT NECHES	State or Country TEXAS
			Zip Code 77651
Full Name of Inventor	Last Name TATTERSALL	First Name THOMAS	Middle Name A.
	Signature (please sign full name):		Date:
Residence & Citizenship	City WILMINGTON	State or Foreign Country DELAWARE	Country of Citizenship U.S.A.
Post Office Address	Post Office Address 22 LONGSPUR DRIVE	City WILMINGTON	State or Country DELAWARE
			Zip Code 19808
Full Name of Inventor	Last Name WOLFF	First Name MARK	Middle Name C.
	Signature (please sign full name):		Date:
Residence & Citizenship	City EDGEWOOD	State or Foreign Country KENTUCKY	Country of Citizenship U.S.A.
Post Office Address	Post Office Address 710 HURSTBORNE LANE	City EDGEWOOD	State or Country KENTUCKY
			Zip Code 41017

■ Additional Inventors are being named on separately numbered sheets attached hereto.